

Verlatex Lumina FR

Soluții pentru publicitate și decor

BRIEF DESCRIPTION

- 100% polyester woven fabric with tight structure
- Smooth surface, soft hand feeling, good wrinkle-resistance
- Ideal as light box, also can be used as indoor decoration, display, etc

FEATURES











INK PRINTABILITY





MATERIAL DETAILS

Properties	Teste method	Metric	Imperial
Total Weight	DIN EN ISO 2286-2, ASTM D751	190 g/sq.m	5.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	100%polyester
Weave Method	N/A	Woven	
Shrinkage	210 °C, 30s	≤2%	
Light Transmittance	ANSI PH2.19, ISO 5/2	42%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1 EN13501-1	DIN 4102-1-B1, NFPA 701 Test1 EN13501-1	
Recommend Fixation Temperature	N/A	190°C-210°C, 1-2min	
Yellowing Temperature	SUPRKC REX-C400, 30s	≥210°C	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320 cm	126"
Standard Lenght	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All of the Information above shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data is available as test results and should not be used for the purpose of a lawsuit or warranty.





