

General Information

Reflexite® GP400 / 800 / 801 Series tapes are tough weather and solvent resistant tapes designed to be used on High Visibility Garments.

For more information on GP 400 /800 / 801 Series tapes, please reference Technical Product Bulletins which are available from your ORAFOL representative.

Sewing to Garment Background Fabric

Sewing Machine Settings

Recommended stitches per cm: 8 per 25 mm. Reduce pressure on the sewing machine foot and/or use a teflon coated foot. Use of a silicone spray or silicon coated cloth will help to lubricate the surface of the tape.

Background Fabric

Whilst ORAFOL has carried out compatibility checks to most of the readily available background fabrics, we cannot give an open guarantee that the chosen background fabric is fully compatible. Please check with the manufacturer of the fabric before use.

General

Do not stretch the tape as it is being applied. ORAFOL recommends that the tape is turned under and sewn through the doubled over edge. This helps prevent moisture ingress. Where possible within the design of the garment the cut ends should be inside the seams of the garment.

IMPORTANT NOTICE

All Reflexite® and ORALITE® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning Reflexite® and ORALITE® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of Reflexite® and ORALITE® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

Reflexite® is a registered trademark of ORAFOL Europe GmbH.

