

POLI-FLEX® SPORT

Product Information

POLI-FLEX SPORT is a matt, reflection-free textile transfer film with a pleasant textile touch, coated with heat sealing adhesive for transfer onto garments. POLI-FLEX SPORT excels due to perfect wash and colour stability.

POLI-FLEX SPORT is suitable to transfer onto textiles such as cotton, polyester/cotton blends and polyester/acrylic. It can be used for lettering on T-shirts, sports and leisure wear, as well.

POLI-FLEX SPORT can be cut with all current plotters. We recommend using a standard 45° knife. After weeding the cut flex film is transferred by a heat press. The PET liner should be removed warm.

Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using POLI-FLEX NYLON.

The soft, elastic flex film offers a comfortable textile touch and convinces due to high wearing comfort. POLI-FLEX SPORT excels due to an excellent opacity. POLI-FLEX SPORT is covered with a non-adhesive liner, enabling the stacking of weeded decals. The non-adhesive PET liner guarantees perfect cutting, even the smallest details can be weeded without any problem.

Guarantee for a secure and long-lasting bond of POLI-FLEX SPORT is only given when following the specified temperature and pressure conditions.

We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability can only cover the unprocessed material.

Technical Data

Transfer Film:	PU/PVC,	cast	
Adhesive:	Polyurethane-hotmelt		
Thickness [mm]:	0,18 0,28	+/- 5 % +/- 5 %	(Standard) (Neon)
Liner:	PET-film,	non-adhes	ive

Transfer Conditions

Temperature:	130 °C (Standard Colors) 160 °C (Neon Colors + 4460)
Pressure:	3,5 bar [medium pressure]
Time:	10 sec.

Wash Resistance

Wash resistance:	40 °C
	Suitable for dry-cleaning;
	Perchloroethylene (Tetrachloroethylene).
	Wash textile inside out.

Standard Dimensions

500 mm x 25 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

24/03/2015

POLI-TAPE Klebefolien GmbH Zeppelinstraße 17 53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37

E-Mail: info@poli-tape.de Internet: www.poli-tape.de The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.