

## Description

This mounting tape consists of a white, closed-cell polyethylene foam coated on both sides with a rubber adhesive. It adheres well among other things on apolar substrates. Its adhesive is lined with a white double-sided silicone paper.

## Carrier

Closed-cell polyethylene foam, white, 1000 micron

## Liner

White paper, 90 g/m<sup>2</sup>, both sides coated with silicone

## Adhesive

Rubber

## Area of use

For fixing of boards, displays and for a variety of household applications. A universal, economical product. Good adhesion also on rough surfaces.

## Technical data

<b>Thickness*</b> (foam and adhesive)	1100 micron
<b>Density*</b>	58 kg/m <sup>3</sup>
<b>Temperature resistance***</b>	-30°C to +70°C
<b>LoopTack*</b> (FINAT TM 9)	35 N/25mm
<b>Adhesive power*</b> (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min 18 N/25mm after 20 min > 18 N/25mm, foam tear after 24 h > 18 N/25mm, foam tear
<b>Shear strength*</b> (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 500 h at 23°C 1 h at 70°C
<b>Temperature resistance*</b> (S.A.F.T.)	75°C
<b>Shelf life**</b>	1 year
<b>Application temperature</b>	> +15°C

\* average

\*\* in original packaging, at 20°C and 50% relative humidity

\*\*\* 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.