

Description

This double-sided tape consists of a hard PVC film carrier, layered on both sides with a modified solvent acrylate adhesive. It has a very good resistance against UV radiation, extreme temperatures, chemicals, solvents and humidity. Its highly shear-resistant adhesive has excellent durability when attached to metal, varnish and high energy surfaces. It has a good adhesive durability when attached to low energy surfaces. Because of its high adhesive mass it is also appropriate for rough or structured surfaces.

Carrier

Hard PVC film, white, 38 micron

Liner

Brown paper, both sides coated with silicone, 90 g/m²

Adhesive

Modified solvent acrylate

Area of use

Used for the secure attachment of truck and car mirrors in plastic housings. Used as an adhesive medium for signs as well as for extruded synthetic profiles and for durable installation in the furniture industry. Used for the attachment of trims, bars and laminates to a variety of surfaces. For the fixing of covers and handles in the audio, household appliance and electrical industry.

Technical data

Thickness* (carrier and adhesive)	260 micron	
Temperature resistance***	-40°C to +70°C	
Resistance to solvents and chemicals	with expert application resistant to most oils, grease, fuels, aliphatic solvents, weak acids, salts and alkalis	
LoopTack* (FINAT TM 9)	23 N/25mm	
Adhesive power* (FINAT TM 1, stainless steel, one side covered with 50 micron polyester film)	32 N/25mm	after 1 min
	36 N/25mm	after 20 min
	38 N/25mm	after 24 h
Shear strength* (FINAT TM 8, stainless steel, one side covered with 50 micron polyester film)	> 400 h	at 23°C
	> 6 h	at 70°C
Temperature resistance* (S.A.F.T.)	100°C	
Shelf life**	2 years	
Application temperature	> +15°C	

* average ** in original packaging, at 20°C and 50% relative humidity

*** 1h, normal climate of Central Europe

The statements in this information sheet are based upon our knowledge and practical experience. This data is intended only as a source of information and is given without guarantee and does not constitute a warranty. Due to the wide variety of possible uses and applications customers should independently determine the suitability of this material for their specific purpose, prior to use.



ORAFOL Europe GmbH - Orafolstraße 2 - D 16515 Oranienburg
Telefon: +49 (0) 33 01/864 0 - Telefax: +49 (0) 33 01/864 100
E-Mail: verkauf@orafol.de - Internet: <http://www.orafol.de>