

Easy Punto Pro

A 100 micron monomeric matt white **high opacity** self-adhesive PVC film with a permanent dot shaped adhesive for easy repositioning.

Suitable for Latex UV and (eco) solvent based inks.

The adhesive increasingly will be **stronger** after being applied.

This product can be handled and applied by anyone without special knowledge

- ✓ High Quality Printable
- ✓ Adhesive color: transparent
- ✓ Reworkable, semi-removal
- ✓ Application surface: flat or curved
- ✓ Surface: matte

Property	Metric Units	Test Method
Width	54"	
Length	30m (100ft)	
Core	3"	
Thickness(w/ adhesive)	130 μ m \pm 10%	Micrometer
Tensile Strength	225kg/cm ²	ASTM D638
Elongation	289%	ASTM D639
Adhesive	Initial 20 min. \geq 700 g/in middle 1days \geq 900 g/in Final 3 days \geq 1,100 g/in	180 peeling
Service temp.	-45°C ~ 82°C	
Transparency	\pm 0.5	Haze Meter
Matte	25° \geq	
Release liner's Thickness	0.14mm / 90g/m ² \pm 10%	

Compatibility

Ink Compatibility: Eco-Sol, Solvent, Latex, UV

Application:

Promotion / Exhibition Hall Printings
In/Outdoor Industrial Advertising

Guidelines:

Printing Tip: Suitable printing condition: Temperature 15~30°C(59~86°F) / Humidity 40~60%

Use care in handling printed material, surface susceptible to abrasion

To optimize the printing quality, printer need to be set for highest print quality.

Lamination: Lamination is optional. In order to protect the image from physical damage and to decrease image-fading, Overlamine is recommended.

Storage: It is recommended to store in the closed original packing in a cool and dry environment. Temperature 10°~25°C (50°~77°F), Relative Humidity 50% RH