

PRODUCT INFORMATION

Mod. R&S.	Rev.	Last updated	Pag.
05	03	12/2015	1 di 1

SOFT PRINT COLOR MATT

Description

Matt PU heat seal material with polyester backing, created for inkjet digital printing & cutting systems with solvent or eco solvent inks. Despite being very thin, the material grants a high covering power on dark fabrics.

Average film thickness before transfer: 45 micron

Usage informations

Due to the many different base materials available on the market, the following

instructions are given as a guideline only: Plotter settings (eg. with ROLAND VP-300)

Blade: new at 50°

Minimum cutting pressure: 60 gf

Transfer setup

Temperature: 155 °C (310°F)

Time: 15 seconds

Pressure: medium (3:4 bar)

Procedure

Print and cut the material. Weed the exceeding material. Wait for drying for at least 4 hours.

Remove the print from the polyester backing using Siser's T.T.D. Easy (adhesive,

transparent and resistant to high temperatures)

Heat apply

Remove the application tape cold.

Certifications

The product is REACH approved

Suitable textiles

Cotton, polyester, Lycra® and blends of these materials (not suited for treated and dye sublimation fabrics)
Wait **24h** after the heat transfer

Washing instructions

40°C

Do not use bleach or other aggressive chemical agents.

Dry clean: no

Tumble dry: not recommended



Siser s.r.l.

N.B. All information given in this sheet are based on our experience. We always recommend performing a test before starting standard production. For best results we recommend to store the product away from direct sunlight.

Viale della Tecnica n° 18 36100 Vicenza - Italy Tel. +39 0444.287960 Fax +39 0444.287959 info@siser.it - www.siser.it

The product meets the Italian and EU regulations relating to its proper use, and to the (EU) regulation n. 1907/2006/EU REACH (Registration, Evaluation, Authorization and Restriction of Chemical substance). This document can be subject to variations. Updated versions are available on our website www.siser.it. For further information, please contact our Sales Office. Thank you.