

Description

This tape consists of white, closed-cell polyolefin foam coated on both sides with a modified polyacrylate adhesive. This modified polyacrylate adhesive possesses a high initial adhesion and high shear strength.

Carrier

Closed-cell polyolefin foam, white, 1000 micron

Liner

PP-film, yellow, both sides coated with silicone, 100 micron

Adhesive

Modified solvent acrylate

Area of use

For the installation of smooth spray cast and extruded plastic parts such as panels, bars and signs, as well as plexiglass mirrors for interior fit-outs and displays. For use as an adhesive medium for hooks, holders and dispensers on smooth surfaces. Due to good UV, water and age resistance this product is also suitable for exterior applications.

Certificates

The tape is certified according to UL 746C.

Technical Data

Thickness* (foam and adhesive)	1100 micron
Density* (foam)	55 kg/m ³
Temperature resistance***	-40° C to +80° C
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	after 1 min: >17 N/25 mm after 20 min: >18 N/25 mm, tear after 24 h: >18 N/25 mm, tear
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	at 23° C: > 300 hours at 70° C: > 3 hours
Shelf life**	2 years
Application temperature	> +15° C

* average ** in original packaging, at 20°C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORAMOUNT® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAMOUNT® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAMOUNT® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORAMOUNT® is a registered trademark of ORAFOL Europe GmbH.