

Product Information

1200 µm double sided PE foam tape

tesa® 55576 is a double sided PE foam tape for light duty mounting applications. It consists of a PE foam backing and a tackified acrylic adhesive, covered with a red film liner.

Main Application

- Trims & Profiles Mounting
- POS Signs & Advertising Material Mounting
- Mirror Pre-Mounting
- Temporary Mounting
- Gap Filling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PE foam	• Tensile strength	10 N/cm
• Total thickness	1200 µm	• Type of liner	PE
• Type of adhesive	tackified acrylic	• Color of liner	red
• Elongation at break	50 %	• Thickness of liner	70 µm

Adhesion to

• Steel (initial)	5.5 N/cm	• PE (initial)	1.4 N/cm
• Aluminium (initial)	6.4 N/cm	• PVC (initial)	3.0 N/cm

Properties

• Temperature resistance short term	80 °C	• Static shear resistance at 40°C	●
• Temperature resistance long term	60 °C		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

tesa® 55576

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=55576>