





- . Double linear guide and strengthed carriage bean to ensure the best movement, perfectly locates the prints either on hard or flexible material at difference limited within 0.02-0.05mm.
- · Anti-static devices equipped to eliminate bad influence from printing
- Print head auto capping system, auto height adjustment, individual color channel to purge
- Selected top-standard conveyor belt to ensure printout without any mistake on deviation&wrinkle&belt mark.
- Electronic control shift for platform suction & blower, easy load & unload the media
- Suction control by flow-meter automatically to be the same with extreme material like very thin, very soft, etc.
- · White ink recycling system to keep white printing consistency and none of blockage
- Double negative pressure system for colors and white respectively, to keep the fluency

## **Description**





LED UV curing system



THK linear guide



IGUS Chain



Big printhead carriage



Electronic magnetic valve



Printhead anti-crash system



High quality conveyor belt to avoid media wrinkle&deviation



Print head capping devices



Airshaft for media feeding & taking up



Suction control devices



Frequency flow suction



## Technical Specification

Print Model HUNTER 2000UV HUNTER 3200UV Print Size 2050mm\*extension table 3200mm\*extension table Print Head 4~9 industrial print head High Speed 60sqm/h 75sqm/h Production 50sqm/h 57sqm/h CMYK+W CMYK+W Quality 28sqm/h 39sqm/h Super 22sqm/h 28sqm/h Resolution Up to 1200dpi Print Technology Piezoelectric inkjet, Grayscale Technology Ink Types LED UV curable ink Ink Configuration Standard CMYK, Lc, Lm, White, Vanish(Optional) Ink cartridge size 2.5 Liter Image process Software Aurelon, Caldera, Onyx Optional Color management ICC based color, adjustment curves, density adjustment Operating System Windows 10 64bits USB2.0/3.0 Hard Ware 500G+ File format Tiff, Jpeg, Postscript, EP/ PDF, etc Media Media Thickness 0-5cm Divided into 4 / 5 independent suction area for various media size printing Platform Vinyl, PET film, Back lit, Synthetic paper, Banner, Acrylic, glass etc. Media Ink Supply Negative pressure system Ink level sensor to alarm **Curing System** LED UV lamps Dimensions Printer 4392mm(L)\*1515mm(W)\*1500mm(H) 5692mm(L)\*1665mm(W)\*1623mm(H) Package 4600mm(L)\*2270mm(W)\*1930mm(H) 5800mm(L)\*2200mm(W)\*1800mm(H) Weight 1500 KG 2000 KG Printer 2000 KG Package 2500 KG **Operating Conditions** Temperature 20 to 30°C Relative Humidity 30% - 70%, non-condensing **Electricity Request** 6000W 28A Power Requirements 220 VAC, single-phase, 50Hz Warranty

One year limited warranty(Please contact your local dealer for details)





## HUNTER 2000UV / HUNTER 3200UV

1200 DPI VDS 2.05m\*/3.2m\* extension table